

Strapping Machine



BENEFITS :

- * Time Saving
- * Man hour Saving
- * Material Saving
- * Better packing impact

Silent Features :

- * Instant heating in just 20 second.
- * Magnetic drive for faster & speed / packing.
- * Lift type top cover allows convenient maintenance.
- * Safety switch is activated as soon as top cover is opened.
- * Economic design of control switch, independent PCB control feeding and heating. The unit is easy to maintain.
- * External adjustable tension knob on control panel provides easy and simple operation.
- * One touch machine operation energy saving mode activates in just 15 sec of non-use and allows for instant operation.
- * Stainless steel frame is available for strapping moisturised products.



TECHNICAL SPECIFICATIONS:

	Heigher Table	Lower Table
Strap Cycle Speed	1.5 Sec./ strap	1.5 Sec./ strap
Strap Width	6 to 15 mm	6 to 15 mm
Sealing Method	Heat Sealed	Heat Sealed
Min. Package Size	60 mm (W)	60 mm (W)
Driving Motor	250 V X 1(¼ H.P.)	250 V X 1(¼ H.P.)
Power Supply	220 V 50 / 60 Hz, 1 Phase	220 V 50 / 60 Hz, 1 Phase
Tension Strength	55 Kg./ Max.	55 Kg./ Max.
Machine Weight	above 100 Kg.	above 90 Kg.
Dimension	900 x 580 x 750	1450 x 580 x 505

• Manufacturer reserves all rights to change product specification & its design without prior intimation.

